

### SIZE EEL16 · OUTPUT : 18W

Primary / Secondary Insulation  $\geq 2000\text{Vac}$

Ambient temperature  $< 60^\circ\text{C}$

Construction conforms to IEC950,IEC335,IEC61558 for reinforced insulation

Exclusively uses UL94-V0 listed materials

Dimensions and Diagram (Unit mm +/-0.5mm):		Circuit Diagram:				
Output Power	Windings					
		Pins	Turns	Inductance (+/-15%)	Resistance max. ( $\Omega$ )	
	<b>18 W</b>	Pri.	9 to 10	140	1.4 mH	5.0
		S1	2 to 3	33		0.2
S2		4 to 6	11		0.1	
	Aux.	8 to 7	19		0.2	

### SIZE EF12.6 · OUTPUT : 8W

Primary / Secondary Insulation  $\geq 1500\text{Vac}$

Ambient temperature  $< 60^\circ\text{C}$

Construction conforms to IEC950,IEC335,IEC61558 for reinforced insulation

Exclusively uses UL94-V0 listed materials

Dimensions and Diagram (Unit mm +/-0.5mm):		Circuit Diagram:				
Output Power	Windings					
		Pins	Turns	Inductance (+/-15%)	Resistance max. ( $\Omega$ )	
	<b>8 W</b>	Pri.	1 to 5	76	0.55 mH	1.0
		Aux.	2 to 4	7		0.2
S1		6 to 10	10		0.3	